LOAN DOCUMENT

PHOTOGRAPH THIS SHEET	
LEVEL INVENTORY WOLK Plan for Birsenting Justem Removal BOCUMENT IDENTIFICATION Hug 910	
DISTRIBUTION STATEMENT A Approved for Public Release Distribution Unlimited	
DISTRIBUTION STATEMENT	
DISTRIBUTION STAMP	
DATE RETURNED	
20001129 076 DATE RECEIVED IN DITIC REGISTERED OR CERTIFIED NUMBER	
PHOTOGRAPH THIS SHEET AND RETURN TO DTIC-FDAC	
IC ROW 70A DOCUMENT PROCESSING SHEET PREVIOUS EDITIONS MAY BE USED UNTIL	

LOAN DOCUMENT

DEFENSE TECHNICAL INFORMATION CENTER

REQUEST FOR SCIENTIFIC AND TECHNICAL REPORTS					
Title AFCEE Collection					
	annungang-				
1	Report Availability (Please check one box)	2a. Number of Copies Forwarded	2b. Forwarding Date		
	·				
<u> </u>	This report is not available. Complete section 3.	1 each	July/2000		
	Distribution Statement (Please check ONE DOX)		0		
DaD Directive 5230.24, "Distribution Statements on Technical Documents," 18 Mar 87, contains seven distribution statements, as described briefly below. Technical documents MUST be assigned a distribution statement.					
M	DISTRIBUTION STATEMENT A: Approved for public rel	ease. Distribution is u	ınlimited.		
	DISTRIBUTION STATEMENT B: Distribution authorized	to U.S. Government /	Agencies only.		
a	DISTRIBUTION STATEMENT C: Distribution authorized to U.S. Government Agencies and their contractors.				
	DISTRIBUTION STATEMENT D: Distribution authorized to U.S. Department of Defense (DoD) and U.S DoD contractors only.				
	DISTRIBUTION STATEMENT E: Distribution authorized to U.S. Department of Defense (DoD) components only.				
	DISTRIBUTION STATEMENT F: Further dissemination a indicated below or by higher authority.	DISTRIBUTION STATEMENT F: Further dissemination only as directed by the controlling DoD office indicated below or by higher authority.			
	DISTRIBUTION STATEMENT X: Distribution authorized to U.S. Government agencies and private individuals or enterprises eligible to obtain export-controlled technical data in accordance with DoD Directive 5230.25, Withholding of Unclassified Technical Data from Public Disclosure, 6 Nov 84.				
2d. Reason For the Above Distribution Statement (in accordance with DoD Directive 5230,24)					
2ė.	Controlling Office	2f. Date of Distr	ribution Statement		
	HQ AFLEE		V 2000		
₹3.	This report is NOT forwarded for the following reason.	s. (Please check appropr	rate box)		
		date) and the AD numbe			
	It will be published at a later date. Enter approximate dat	*	71 100		
		***************************************	TO THE PARTY OF TH		
	THE BEATH OF THE PROPERTY OF T	- Annual Control of the Control of t	A CONTRACTOR OF THE CONTRACTOR		
Prin	nt or Type Name Signa	ture			
La	rura Pena	aura Le	Ina		
	ephone 10 - 536 - 1431	(For DTIC Use Of AQ Number			

Cost? Base Approval?

PARSONS ENGINEERING SCIENCE, INC.

1700 Broadway, Suite 900 • Denver, Colorado 80290 • (303) 831-8100 • Fax: (303) 831-8208

fer telecon 22 Angbase approved work. Esty Cost estimate by 6 sep Esty

August 8, 1996

Captain Ed Marchand AFCEE/ERT 3207 North Road, Bldg. 532 Brooks AFB, Texas 78235-5363

Subject:

Work Plan for Bioventing System Removal and Well Abandonment at Sites 204.1, 228, and 510.8, Hill Air Force Base (AFB), Utah (Contract Number F41624-92-8036, Delivery Order 17)

Dear Captain Marchand:

This letter includes a brief work plan for bioventing system removal and the abandonment of vent wells (VWs), groundwater monitoring wells (MWs), and vapor monitoring points (VMPs) at Sites 204.1, 228, and 510.8. The bioventing system at Site 924 has already been removed and is not included in this scope of work.

Parsons ES installed bioventing systems at former underground storage tank (UST) Sites 204.1, 228, and 924 in July 1992, and at Site 510.8 in August 1993. Parsons ES and Hill AFB (Base) requested no-further-action site closure letters for these sites from the Utah Department of Environmental Quality, Division of Environmental Response and Remediation (DERR) in July 1995. DERR has recently agreed that the vadose zone soils at these sites have been sufficiently remediated, and closure letters have been issued by DERR. The remediation effort will be completed with the removal of the bioventing systems and abandonment of VWs, MWs and VMPs at the sites referenced above.

Scope of Work

The general activities to be performed at each site include the following:

Site 204.1

- Disconnect and remove the electrical system associated with the blower unit. This will include removal of electrical components such as the starter and disconnect switch. The overhead wiring will be retained for future use by Hill AFB.
- The regenerative blower and its protective shed will be removed.
- Vent well SB204A-04 will be appropriately abandoned.



AQ MOI-02-0287

- Groundwater monitoring well T-204-1-MW-U-92-HF will be appropriately abandoned.
- Vapor monitoring points SB204A-01, SB204A-02 and SBA204A-03 will be appropriately abandoned.
- The ground surface will be restored.

Site 228

- Disconnect and remove the electrical system associated with the blower unit. This
 will include removal of electrical components such as the starter and disconnect
 switch.
- The regenerative blower and its protective shed will be removed.
- Vent well T-228-2-VW-U-92-HF will be appropriately abandoned.
- As requested by Hill AFB, groundwater monitoring well T-228-3-BH-U-HF will be left intact.
- Monitoring point T-228-1-VP-U-92-HF will be appropriately abandoned.
- The ground surface will be restored.

Site 510.8

- Disconnect and remove the electrical system associated with the blower unit. This will include removal of electrical components such as conduit, starter, and disconnect switch. Subsurface conduit will be abandoned in place.
- The regenerative blower and its protective shed will be removed.
- Vent well 510SVE-1 will be appropriately abandoned.
- As requested by Hill AFB, groundwater monitoring well EA-MW1 will be left intact.
- Monitoring points MPA, MPB and MPC will be appropriately abandoned.
- The ground surface will be restored.

The bioventing system removals and VW, MW, and VMP abandonment for all three sites will be accomplished in one field mobilization. The work will be performed by Parsons ES personnel from the Salt Lake City office and qualified local subcontractors to ensure timely completion of the work. A Utah-certified UST consultant will be in responsible charge of the abandonment activities.

Captain Ed Marchand August 8, 1996 Page 3

Bioventing system removal will involve disconnecting the regenerative blowers from the VW piping and capping the blower outlets to prevent moisture and debris from accumulating in the blower system. The power supply to the blowers will be disconnected and removed by a licensed electrician provided by Parsons ES. The blowers are the property of the Air Force and will be stored at the Base for future bioventing use. Parsons ES will move the blowers to storage or site locations to be designated by the Base.

After the electrician disconnects the power supplies and removes the power switches, any associated wire and conduit connecting the disconnect switches to the site power sources also will be removed. At Site 510.8, buried conduit located between the blower shed and the power source will be abandoned in-place after the wiring is disconnected.

The VWs and MWs will be abandoned following the Utah Department of Natural Resources, Division of Water Rights (DWR) well abandonment procedures outlined in the State of Utah Administrative Rules for Water Well Drillers, 1995 (R655-4-11.4 and R655-4-12.1 through R655-4-12.12). The abandonment procedures require filling the well casings with bentonite grout or a bentonite-based well seal using a grout pipe. Each casing will be excavated and cut off at a depth of 2 feet below ground surface (bgs). The excavated area then will be backfilled with native material or roadbase. The backfill will be compacted to the specifications approved by the Base Civil Engineer, and the area will be restored with appropriate hard-surface material.

In order to cut the VW and MW casings at 2 feet bgs, it will be necessary to excavate an area around each casing large enough to chip out the existing grout annular seal. A Utah-licensed well driller will perform the abandonment of all wells and points, and will file a report of abandonment for groundwater monitoring wells with the DWR. Boreholes have previously been advanced at these locations; therefore it is assumed that no underground utilities are present. However, digging clearances will be requested from Base Red Stakes Services. Construction debris will be disposed of at an offsite public landfill.

The VMPs will be excavated to 2 feet below ground surface as described above for wells. The VMP tubing will be cut off at the bottom of the excavation, and a 0.25" polyvinyl chloride cap will be glued to the top of the casing to be left in place. The excavation will be backfilled with native material or roadbase, and compacted to the specifications approved by the Base Civil Engineer. The area will then be restored with the appropriate hard-surface material.

Parsons ES proposes to perform VW, MP and VMP abandonment n the same field mobilization used for Option 2 closure soil sampling at Site 4301 (projected to occur in October 1996), as described in the Draft Closure Sampling and Analysis Plan for UST Site 4301.0 (EDHL), Little Mountain Test Annex, Hill AFB, Utah. Bioventing system removal could be performed at an earlier date.

Captain Ed Marchand August 8, 1996 Page 4

Please call Mr. Gene Wright, the Parsons ES Site Manager at (801) 572-5999 or Mr. John Ratz, the Parsons ES Project Manager, at (303) 831-8100 if you have any questions regarding this scope of work. It has been a pleasure working on this successful project with Hill AFB Environmental Management and AFCEE.

Sincerely,

PARSONS ENGINEERING SCIENCE, INC.

JWR for Gene Wight

Gene A. Wright, P.G. Certified UST Consultant (CC0020)

John W. Ratz, P.E. Project Manager

cc: File 726876.0921.C